



CARBORUNDUM

ADHESIVES, SEALERS AND COATINGS

Protection Against
the Elements



the definition of
DIFFERENT®

WINDSHIELD ADHESIVE



URETHANE WINDSHIELD SEALER

A one-part urethane adhesive sealant for windshield and backlite installations. Easy handling, fast-set properties, excellent shelf life. Passes Motor Vehicle Safety Standard #212 windshield barrier test and #216 crush test.

| PART # | SIZE | CASE/QTY | V.O.C | COLOR | ELONGATION | SHELF LIFE |
|---------------------|---|----------|-------|-------|--------------|------------|
| 055395 99447 | 11 oz Cartridge, Net Wt. 10.5 fl. oz / 310 ml | 12 | 5% | Black | 300% at 72°F | 1 year |

PRIMER



ZINC-RICH WELD-THROUGH PRIMER

Aerosol primer for use on bare metal parts before welding. This zinc rich primer provides excellent conductivity to minimize weld spatter. It is fast drying, resists sags and settling, is water resistant after 15 minutes and may be topcoated, if desired. Heat resistant up to 500°F. Apply to metal surface either before or after welding to restore OEM zinc corrosion protection. It is formulated to be V.O.C. compliant in California.

| PART # | SIZE | CASE/QTY | V.O.C | MIR | COLOR | SHELF LIFE |
|---------------------|---|----------|-------|------|-------------|------------|
| 055395 99452 | 16 oz Aerosol, Net Wt. 13.75 fl. oz / 390 grams | 12 | 48% | 0.83 | Silver Gray | 1 year |

SEAM SEALERS



URETHANE SEAM SEALER

A one-component, polyurethane seam sealer that cures quickly to a permanent, flexible sealant. Designed for sealing both interior and exterior automotive or RV body joints and seams, duplicating the OEM appearance. Can be smoothed to a featheredge and/or brushed and will not shrink or crack. Paintable in 1 hour. Flexible foil package eliminates product waste. Use with Application Gun #82786.

| PART # | SIZE | CASE/QTY | V.O.C | COLOR | SHELF LIFE |
|---------------------|----------------------------|----------|--------------------|-------|------------|
| 055395 99450 | 10.3 oz foil pack / 305 ml | 6 | 0.49# /Gal (59g/l) | White | 1 year |



APPLICATION GUN FOR 99450

Designed for use with Carborundum Urethane Seam Sealer (#99450). This is a fully enclosed metal unit, which provides fast and efficient application of seam sealer material. Low ratio mechanism allows for easy pumping and precise application of sealant.

| PART # | SIZE | CASE/QTY |
|---------------------|---------------------------------|----------|
| 076607 82786 | fits 10.3 oz (305 ml) foil pack | 6 |



Protecting a vehicle against the elements is part of a quality repair. Sealing out wind, water and noise is no easy task, but VOC compliant, high quality products from the Carborundum line of Adhesives, Sealers and Coatings are up to the challenge.

CLEANERS



PANEL AND ADHESIVE CLEANER

Removes adhesives, tar, grease, wax, body sealers, undercoating sprays, and silicone from most surfaces. Aggressive cleaner is safe to use on most paint applications. Packaged with squirt dispenser. Use as directed.

| PART # | SIZE | CASE/QTY | V.O.C | SHELF LIFE |
|-------------|----------------------------|----------|--------------------|------------|
| 05539599459 | Quart / 32 fl. oz / 946 ml | 12 | 0.00# /Gal (0 g/l) | 1 year |

COATINGS



ROCKER-PANEL TEXTURE COAT

A rapid drying, flexible, abrasion resistant protective coating that can be varied to match OEM textures found on rocker panels and valances. Paintable in 60 minutes. Highly chip resistant.

| PART # | SIZE | CASE/QTY | V.O.C | MIR | COLOR | SHELF LIFE |
|-------------|--|----------|-------|------|-------|------------|
| 05539599453 | 16 oz Aerosol, Net Wt. 13 fl. oz / 369 grams | 6 | 55% | 1.16 | White | 1 year |
| 05539599454 | 16 oz Aerosol, Net Wt. 13 fl. oz / 369 grams | 6 | 59% | 1.17 | Black | 1 year |



PREMIUM RUBBERIZED UNDERCOAT – PAINTABLE

Paintable and fast-drying rubberized undercoat for rust-prevention, sound deadening and chip resistance to fenders, undercarriages, quarter panels, wheel wells, decks and hoods. Excellent adhesion to painted and unpainted surfaces. Resists rust and abrasion as it seals out dust and moisture.

| PART # | SIZE | CASE/QTY | V.O.C | COLOR | SHELF LIFE |
|-------------|---|----------|---------------|-------|------------|
| 05539599455 | 24 oz Aerosol, Net Wt. 17.75 fl. oz / 503 grams | 6 | Less than 40% | Black | 1 year |



RUBBERIZED UNDERCOAT

Seals out rust, fumes, heat and cold while protecting underbody areas. Excellent adhesion that won't crack or chip under normal conditions. Engineered to protect underbody areas from moisture and abrasion while deadening sound. Fast drying and economical.

| PART # | SIZE | CASE/QTY | V.O.C | COLOR | SHELF LIFE |
|-------------|--|----------|---------------|-------|------------|
| 05539599456 | 20 oz Aerosol, Net Wt. 16 fl. oz / 454 grams | 6 | Less than 40% | Black | 1 year |

SPECIALTY COATING



CARBON BLACK GUIDE COAT

Provides the technician with a visual aid to ensure primed surfaces are totally smooth and even. A quick and efficient method to find uneven and low spots on body filler, primer, glazing putties and other repair components.

| PART # | SIZE | CASE/QTY | V.O.C | MIR | COLOR | SHELF LIFE |
|---------------------|---|----------|-------|------|-------|------------|
| 055395 99457 | 16 oz Aerosol / Net Wt. 10.5 fl. oz / 297 grams | 6 | 38% | 0.62 | Black | 1 year |



BLACK POWER GUIDE COAT

Ideal for identifying imperfections in primer and body filler that need to be sanded out to ensure a flat finish. Simply apply the applicator with the Black Powder Guide Coat over the area to be sanded, and continue sanding until the powder is no longer visible on the surface. This product does not have a dry time and can be sanded immediately, and it can be sanded using either wet or dry sanding methods.

| PART # | SIZE | CASE/QTY | COLOR |
|---------------------|-----------|----------|-------|
| 055395 53346 | 100 grams | 6 | Black |

ATTACHMENT TAPE



PREMIUM AUTOMOTIVE ATTACHMENT TAPE

High-density gray foam tape coated with high strength acrylic adhesive on both sides and a red polyethylene release liner is designed for bonding medium to large moldings and accessories. High strength acrylic adhesive provides superior adhesion to plastics, metal, glass and painted vehicle surfaces.

- Used for attaching body side moldings, cladding, door edges, emblems, interior trim, rocker panel moldings, and pillar covers
- Remains flexible at low temperatures

| PART # | WIDTH | DESCRIPTION | CASE/QTY |
|---------------------|-------|--------------------------|----------|
| 055395 67381 | 1/4" | 20 Yard Roll .045" Thick | 12 |
| 055395 67378 | 1/2" | 20 Yard Roll .045" Thick | 12 |
| 055395 67379 | 7/8" | 20 Yard Roll .045" Thick | 12 |



CARBO ATTACHMENT TAPE ADHESION PROMOTER

Carbo Attachment Tape Adhesion Promoter is a liquid primer to improve the adhesion of Carbo automotive attachment tapes to exterior and interior trims involving injection molded and/or plastics (TPO, PPO, PP, PC, etc.). The convenient dauber style container neatly dispenses the ideal amount of product for optimal adhesion.

| PART # | SIZE | DESCRIPTION | CASE/QTY |
|---------------------|-------|-------------|----------|
| 055395 53395 | 4 oz. | Dauber | 6 |

CABINET



ADHESIVES AND SEALERS CABINET

Heavy-gauge steel will hold all of the Carborundum adhesives and sealers, keeping them clean, dry, and secure.

| PART # | SIZE | CASE/QTY |
|---------------------|-----------------|----------|
| 055395 99365 | 30" x 10" x 26" | 1 |

CARBO™

the definition of **DIFFERENT®**

facebook.com/carboauto | youtube.com/carboauto | carbo.com

CUSTOMER SERVICE:

USA Toll Free: 1 (877) 447-5359
Canada Toll Free: 1 (800) 263-6565

FORM #CA5233 REV. 08/17

© Saint-Gobain August 2017.
The Carborundum logo is a registered trademark; The Definition of Performance is a trademark of Saint-Gobain.
Vehicle image provided courtesy of Ford Motor Company.



A Saint-Gobain Brand



Accredited Training Provider