



PART NUMBER

Carborundum Panel and Adhesive Cleaner

055395**99459**

PACKAGE SIZE

Quart/32 oz.

12/case

DESCRIPTION

Removes adhesives, tar, grease, wax, body sealers, undercoating sprays, and silicone from most surfaces. Aggressive cleaner is safe to use on most paint applications. Packaged with squirt dispenser. Use as directed.

APPLICATION

1. Apply to surface prior to grinding, sanding or painting to prevent contaminants from being worked into the substrate surface
2. Saturate a clean cloth
3. Work small areas rubbing briskly
4. Wipe off immediately with a clean, dry cloth
5. Change cloths frequently to prevent spreading of contamination
6. If necessary, repeat entire application until completely clean

Note: For best results, wipe dry, do not let evaporate on panel.

SUBSTRATES

Bare Steel, Bare Galvanized, Bare Aluminum, OEM E-Coat, Raw Plastic- Rigid, Flexible, Soft, Body Filler, Primer- Self-Etch, 1K, 2K

TECHNICAL DATA

MIXING: Ready to Use

APPEARANCE: Clear Liquid

SHELF LIFE: 1 Year

REGULATORY

CATEGORY: CLEANER

VOC Actual:	0.00#/gal (0.00 g/l)	Weight % of Exempt Compounds	100
VOC Regulatory:	0.00#/gal (0.00 g/l)	Volume % of Exempt Compounds	100
Weight % of Volatiles	100	Density of Material #/gal	11.13
Weight % of Water	0		

PRECAUTIONS

For professional use only. Before use, read and follow all TDS, label and SDS precautions.

