

**PART NUMBER**

Carborundum Rocker-Panel Texture Coat  
055395**99453**

**PACKAGE SIZE**

16 oz. Can/13 oz. Net Weight

**DESCRIPTION**

A rapid drying, flexible, abrasion-resistant protective coating that can be varied to match OEM textures found on rocker panels and valances. Paintable in 60 minutes. Highly chip resistant.

**APPLICATION**

1. Clean surface with Carbo Panel and Adhesive Cleaner (055395**99459**)
2. Prepare bare metal with appropriate metal primer
3. Sand with 220 grit. Blow surface clean with air and wipe with Carbo Panel and Adhesive Cleaner (055395**99459**)
4. Shake can vigorously
5. Apply in 1-3 light even coats. Film build should be about 3.0 mils per coat. Total film build should not exceed 8-10 mils
6. Flash 10-15 minutes between coats. IMPORTANT: KEEP CAN IN MOTION WHEN APPLYING TO AVOID EXCESSIVE FILM BUILD
7. Allow final application to flash 30-60 minutes at 75°F (25°C) before topcoating
8. Follow manufacturer's instructions before topcoating



**SUBSTRATES**

Bare Steel, Bare Galvanized, Bare Aluminum, OEM E-Coat, Plastic- Rigid (SMC, BMC), Flexible (ABD, PPO) and Soft (PUR), Body Filler, Primer- self-etch, 1K, 2K

**TECHNICAL DATA**

**APPEARANCE:** White  
**MIXING:** By Volume: Ready to Use  
**FLASH TIME:** 10-15 minutes @ 70°F (21°C)  
**SHELF LIFE:** 1 Year

**REGULATORY**

CATEGORY: ABT	4303	4313
MIR	<1.70	<1.70

**PRECAUTIONS**

For professional use only. Before use, read and follow all TDS, label and SDS precautions.