

PART NUMBER

Carborundum Rubberized Undercoat

055395**99456**

PACKAGE SIZE

20 oz. Can/16 oz. Net Weight

6/case

DESCRIPTION

Seals out dust, fumes, heat and cold while protecting underbody areas. Excellent adhesion that won't crack or chip under normal conditions. Engineered to protect underbody areas from moisture and abrasion while deadening sound. Fast drying and economical.

APPLICATION

1. Shake well
2. Clean surface with Carbo Panel and Adhesive Cleaner (055395**99459**)
3. Holding can 8- 10 inches from surface, apply 2- 3 light even coats. Short, even strokes will produce best results
4. Remove overspray with Carbo Panel and Adhesive Cleaner (055395**99459**)
5. When finished, invert can and spray until valve is free of material to prevent clogging

IMPORTANT: On cars equipped with catalytic converters, exhaust components operate at temperatures exceeding 1000°F (520°C) Therefore, avoid application of undercoating and/ or rust proofing materials within 12" of the exhaust system

SUBSTRATES

Painted or Primed Steel, Bare Steel, Aluminum Wheel Wells, Galvanized Steel, Frame Rails, Bare Aluminum

TECHNICAL DATA

MIXING: Ready to Spray

APPEARANCE: Black

SHELF LIFE: 1 Year

REGULATORY

CATEGORY: UNDERCOAT

VOC Content: <40% by weight

PRECAUTIONS

For professional use only. Before use, read and follow all TDS, label and SDS precautions.

