

**PART NUMBER**

Carborundum Urethane Seam Sealer

055395**99450**

**PACKAGE SIZE**

10.3 fl. oz. (305 ml)

6/case

**DESCRIPTION**

A one-component, polyurethane seam sealer that cures quickly to a permanent, flexible sealant designed for sealing interior and exterior body joints and seams and duplicates OEM appearance. Paintable in 1 hour. Flexible foil package eliminates product waste. Use with Application Gun (076607**82786**)



**APPLICATION**

1. Clean surface with Carbo Panel and Adhesive Cleaner (055395**99459**)
2. Using a razor blade, puncture or cut around the end of sausage pack to remove metal clip
3. Load into application gun (076607**82786**)
4. Apply material as needed. After use, store product in gun

**SUBSTRATES**

Bare Steel, Bare Galvanized, Bare Aluminum, Primer- Self-Etch, 1K, 2K

**TECHNICAL DATA**

**PAINT TIME:** 1 Hour  
**CURE TIME:** 24 Hours  
**APPEARANCE:** White  
**SHELF LIFE:** 1 Year

**REGULATORY**

CATEGORY: SEALANT			
VOC Actual	0.46#/gal (55 g/l)	Weight % of Exempt Compounds	0
Voc Regulatory	0.46#/gal (55 g/l)	Volume % of Exempt Compounds	0
Weight % Volatiles	4.6%	Density of Material #/gal	10.01
Weight % of Water	0		

**PRECAUTIONS**

For professional use only. Before use, read and follow all TDS, label and SDS precautions.